

itcoprime™
Primer for Solvent Based Traffic Markings

Introduction

itcoprime™ Primer for Solvent Based Traffic Markings is a specially formulated primer recommended for application on concrete and asphalt road surface prior to the application of Solvent Based Traffic Markings

Test	Unit	Specification
Appearance	-	Clear liquid
Specific Gravity @ 30°C	gm/cc	0.92 ± 0.03
Viscosity by Fordcup B4 @30°C	Seconds	20 ± 5
Typical Properties (Will not be reported on COA)		
Solid Content	%	30 ± 2
Dry time, Surface dry	Minutes	Max. 30
Dry time Tack Free/recoat	Minutes	Max. 60

Theoretical Coverage

- At wet film thickness of 25 microns = approx. 40 square meters per litre
- At wet film thickness of 50 microns = approx. 20 square meters per litre

Recommended Uses

- Concrete - Kerbs and Dividers, Parking Lots, Roads, Industrial Premises and Shopping Malls

Application Conditions

- Before applying coatings ensure the surface is clean and dry. Also it should be free of oil, grease, gasoline and moisture
- Substrate temperature should be above 10°C and less than 80% humidity

Packaging

20 Litres MS drum

Storage

Store containers tightly closed in a dry and cool place at a temperature below 30°C (86°F), away from any source of fire or sparks

Shelf Life

Best utilized within 6 months of delivery but remains stable for 12 months if unopened and store as recommended

Reference No: ITSC/P-00086	Issue Date: May 15, 2018	Prepared By : Prachi Pimparkar	Date: 08/08/2019
Revision No: 01	Revision Date: August 8, 2019	Approved By : Deepali Nikam	Date: 08/08/2019

Disclaimer: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall ITS Coatings Pvt. Ltd. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ITS Coatings Pvt. Ltd. has been advised of the possibility of such damages.

Head office
10-11, Creative Estate
N.M. Joshi Marg
Lower Parel (E)
Mumbai 400 011, INDIA
CIN No: U24233MH2012PTC229437

T: +91-22- 4054 6474
F: +91-22- 4054 6400
E: sales@itherm.in
W: www.itscoatings.in

Chennai Office
T: +91-44-26801165/75

ISO 9001:2015 Certified

